

MAXIM

Precision, Micropower, Low-Dropout, High-Output-Current, SOT23 Voltage References

General Description

The MAX6061–MAX6068 are precision, low-dropout, micropower voltage references. These three-terminal devices are available with output voltage options of 1.25V, 1.8V, 2.048V, 2.5V, 3V, 4.096V, 4.5V, and 5V. They feature a proprietary curvature-correction circuit and laser-trimmed thin-film resistors that result in a very low temperature coefficient of 20ppm/°C (max) and an initial accuracy of $\pm 0.2\%$ (max). Specifications apply to the extended temperature range (-40°C to +85°C).

The MAX6061–MAX6068 typically draw only 90 μ A of supply current and can source 5mA or sink 2mA of load current. Unlike conventional shunt-mode (two-terminal) references that waste supply current and require an external resistor, these devices offer a supply current that is virtually independent of the supply voltage (8 μ A/V variation) and do not require an external resistor. Additionally, the internally compensated devices do not require an external compensation capacitor. Eliminating the external compensation capacitor saves valuable board area in space-critical applications. Low dropout voltage and supply independent, ultra-low supply current make these devices ideal for battery-operated, high-performance, low-voltage systems.

The MAX6061–MAX6068 are available in a 3-pin SOT23 package.

Applications

- Analog-to-Digital Converters (ADCs)
- Portable Battery-Powered Systems
- Notebook Computers
- PDAs, GPSs, DMMs
- Cellular Phones
- Precision 3V/5V Systems

Typical Operating Circuit appears at end of data sheet.

Selector Guide

PART	OUTPUT VOLTAGE (V)	INPUT VOLTAGE (V)
MAX6061	1.248	2.5 to 12.6
MAX6068	1.800	2.5 to 12.6
MAX6062	2.048	2.5 to 12.6
MAX6066	2.500	(V _{OUT} + 200mV) to 12.6
MAX6063	3.000	(V _{OUT} + 200mV) to 12.6
MAX6064	4.096	(V _{OUT} + 200mV) to 12.6
MAX6067	4.500	(V _{OUT} + 200mV) to 12.6
MAX6065	5.000	(V _{OUT} + 200mV) to 12.6

Features

- ◆ Ultra-Small 3-Pin SOT23 Package
- ◆ $\pm 0.2\%$ (max) Initial Accuracy
- ◆ 20ppm/°C (max) Temperature Coefficient
- ◆ 5mA Source Current
- ◆ 2mA Sink Current
- ◆ No Output Capacitor Required
- ◆ Stable with Capacitive Loads
- ◆ 90 μ A (typ) Quiescent Supply Current
- ◆ 200mV (max) Dropout at 1mA Load Current
- ◆ Output Voltage Options: 1.25V, 1.8V, 2.048V, 2.5V, 3V, 4.096V, 4.5V, 5V
- ◆ 13 μ Vp-p Noise 0.1Hz to 10Hz (MAX6061)


Ordering Information

PART	TEMP. RANGE	PIN-PACKAGE	TOP MARK
MAX6061AEUR-T	-40°C to +85°C	3 SOT23-3	FZFP
MAX6061BEUR-T	-40°C to +85°C	3 SOT23-3	FZFQ
MAX6062AEUR-T	-40°C to +85°C	3 SOT23-3	FZFY
MAX6062BEUR-T	-40°C to +85°C	3 SOT23-3	FZFZ
MAX6063AEUR-T	-40°C to +85°C	3 SOT23-3	FZFV
MAX6063BEUR-T	-40°C to +85°C	3 SOT23-3	FZFW
MAX6064AEUR-T	-40°C to +85°C	3 SOT23-3	FZGB
MAX6064BEUR-T	-40°C to +85°C	3 SOT23-3	FZGC
MAX6065AEUR-T	-40°C to +85°C	3 SOT23-3	FZGE
MAX6065BEUR-T	-40°C to +85°C	3 SOT23-3	FZGF
MAX6066AEUR-T	-40°C to +85°C	3 SOT23-3	FZFM
MAX6066BEUR-T	-40°C to +85°C	3 SOT23-3	FZFN

Note: There is a minimum order increment of 2500 pieces for SOT23 packages.

Ordering Information continued at end of data sheet.

Pin Configuration

**MAXIM**

Maxim Integrated Products 1

For pricing, delivery, and ordering information, please contact Maxim/Dallas Direct! at 1-888-629-4642, or visit Maxim's website at www.maxim-ic.com.

MAX6061-MAX6068

Precision, Micropower, Low-Dropout, High-Output-Current, SOT23 Voltage References

ABSOLUTE MAXIMUM RATINGS

(Voltages Referenced to GND)

IN	-0.3V to +13.5V
OUT	-0.3V to (V_{IN} + 0.3V)
Output Short-Circuit Duration to GND or IN ($V_{IN} < 6V$)	...Continuous
Output Short-Circuit Duration to GND or IN ($V_{IN} \geq 6V$)	...60s

Continuous Power Dissipation ($T_A = +70^\circ C$)

3-Pin SOT23 (derate 4.0mW/ $^\circ C$ above $+70^\circ C$) 320mW

Operating Temperature Range -40 $^\circ C$ to +85 $^\circ C$

Storage Temperature Range -65 $^\circ C$ to +150 $^\circ C$

Lead Temperature (soldering, 10s) +300 $^\circ C$

Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

ELECTRICAL CHARACTERISTICS—MAX6061, V_{OUT} = 1.25V

($V_{IN} = +5V$, $I_{OUT} = 0$, $T_A = T_{MIN}$ to T_{MAX} , unless otherwise noted. Typical values are at $T_A = +25^\circ C$.) (Note 1)

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS
Output Voltage	V _{OUT}	$T_A = +25^\circ C$	MAX6061A (0.32%)	1.244	1.248	1.252
			MAX6061B (0.48%)	1.242	1.248	1.254
Output Voltage Temperature Coefficient (Note 2)	TCV _{OUT}	MAX6061A	6		20	ppm/ $^\circ C$
		MAX6061B	6		30	
Line Regulation	$\Delta V_{OUT}/\Delta V_{IN}$	2.5V $\leq V_{IN} \leq 12.6V$	10		90	$\mu V/V$
Load Regulation	$\Delta V_{OUT}/\Delta I_{OUT}$	Sourcing: 0 $\leq I_{OUT} \leq 5mA$	0.5		0.9	mV/mA
		Sinking: -2mA $\leq I_{OUT} \leq 0$	1.3		3.0	
OUT Short-Circuit Current	I _{SC}	Short to GND	25		mA	
		Short to IN	25			
Long-Term Stability	$\Delta V_{OUT}/\text{time}$	1000hr at +25 $^\circ C$	62		ppm/1000hr	
Output Voltage Hysteresis (Note 3)	$\Delta V_{OUT}/\text{cycle}$		130		ppm	
DYNAMIC CHARACTERISTICS						
Noise Voltage	e _{OUT}	f = 0.1Hz to 10Hz	13		μV_{p-p}	
		f = 10Hz to 10kHz	15		μV_{RMS}	
Ripple Rejection	$\Delta V_{OUT}/\Delta V_{IN}$	$V_{IN} = 5V \pm 100mV$, f = 120Hz	86		dB	
Turn-On Settling Time	t _R	To V_{OUT} = 0.1% of final value, C _{OUT} = 50pF	50		μs	
INPUT CHARACTERISTICS						
Supply Voltage Range	V _{IN}	Guaranteed by line regulation test	2.5	12.6	V	
Quiescent Supply Current	I _{IN}		90	125	μA	
Change in Supply Current	$\Delta I_{IN}/\Delta V_{IN}$	2.5V $\leq V_{IN} \leq 12.6V$	3.4	8.0	$\mu A/V$	

Precision, Micropower, Low-Dropout, High-Output-Current, SOT23 Voltage References

ELECTRICAL CHARACTERISTICS—MAX6068, V_{OUT} = 1.80V

(V_{IN} = +5V, T_A = T_{MIN} to T_{MAX}, unless otherwise noted. Typical values are at T_A = +25°C.) (Note 1)

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS
Output Voltage	V _{OUT}	T _A = +25°C	MAX6068A (0.17%)	1.797	1.800	1.803
			MAX6068B (0.39%)	1.793	1.800	1.807
Output Voltage Temperature Coefficient (Note 2)	TCV _{OUT}	MAX6068A		6	20	ppm/°C
		MAX6068B		6	30	
Line Regulation	ΔV _{OUT} / ΔV _{IN}	2.5V ≤ V _{IN} ≥ 12.6V		33	200	μV/V
Load Regulation	ΔV _{OUT} / ΔI _{OUT}	Sourcing: 0 ≤ I _{OUT} ≤ 5mA		0.5	0.9	mV/mA
		Sinking: -2mA ≤ I _{OUT} ≤ 0		1.5	4	
OUT Short-Circuit Current	I _{SC}	Short to GND		25		mA
		Short to IN		25		
Long-Term Stability	ΔV _{OUT} / time	1000hr at +25°C		62		ppm/ 1000hr
Output Voltage Hysteresis (Note 3)	ΔV _{OUT} / cycle			130		ppm
DYNAMIC CHARACTERISTICS						
Noise Voltage	e _{OUT}	f = 0.1Hz to 10Hz		22		μVp-p
		f = 10Hz to 10kHz		25		μVRMS
Ripple Rejection	ΔV _{OUT} / ΔV _{IN}	V _{IN} = 5V ±100mV, f = 120Hz		86		dB
Turn-On Settling Time	t _R	To V _{OUT} = 0.1% of final value, C _{OUT} = 50pF		115		μs
INPUT CHARACTERISTICS						
Supply Voltage Range	V _{IN}	Guaranteed by line regulation test	2.5	12.6		V
Quiescent Supply Current	I _{IN}		90	125		μA
Change in Supply Current	ΔI _{IN} / ΔV _{IN}	2.5V ≤ V _{IN} ≤ 12.6V	3.3	8.0		μA/V

Precision, Micropower, Low-Dropout, High-Output-Current, SOT23 Voltage References

ELECTRICAL CHARACTERISTICS—MAX6062, V_{OUT} = 2.048V

(V_{IN} = +5V, I_{OUT} = 0, T_A = T_{MIN} to T_{MAX}, unless otherwise noted. Typical values are at T_A = +25°C.) (Note 1)

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS
Output Voltage	V _{OUT}	T _A = +25°C	MAX6062A (0.24%)	2.043	2.048	2.053
			MAX6062B (0.39%)	2.040	2.048	2.056
Output Voltage Temperature Coefficient (Note 2)	TCV _{OUT}	MAX6062A		6	20	ppm/°C
		MAX6062B		6	30	
Line Regulation	ΔV _{OUT} / ΔV _{IN}	2.5V ≤ V _{IN} ≤ 12.6V		33	200	µV/V
Load Regulation	ΔV _{OUT} / ΔI _{OUT}	Sourcing: 0 ≤ I _{OUT} ≤ 5mA		0.5	0.9	mV/mA
		Sinking: -2mA ≤ I _{OUT} ≤ 0		1.5	4	
OUT Short-Circuit Current	I _{SC}	Short to GND		25		mA
		Short to IN		25		
Long-Term Stability	ΔV _{OUT} / time	1000hr at +25°C		62		ppm/ 1000hr
Output Voltage Hysteresis (Note 3)	ΔV _{OUT} / cycle			130		ppm
DYNAMIC CHARACTERISTICS						
Noise Voltage	e _{OUT}	f = 0.1Hz to 10Hz		22		µVp-p
		f = 10Hz to 10kHz		25		µVRMS
Ripple Rejection	ΔV _{OUT} / ΔV _{IN}	V _{IN} = 5V ±100mV, f = 120Hz		86		dB
Turn-On Settling Time	t _R	To V _{OUT} = 0.1% of final value, C _{OUT} = 50pF		115		µs
INPUT CHARACTERISTICS						
Supply Voltage Range	V _{IN}	Guaranteed by line-regulation test	2.5	12.6		V
Quiescent Supply Current	I _{IN}			90	125	µA
Change in Supply Current	I _{IN} /V _{IN}	2.5V ≤ V _{IN} ≤ 12.6V	3.3	8.0		µA/V

Precision, Micropower, Low-Dropout, High-Output-Current, SOT23 Voltage References

ELECTRICAL CHARACTERISTICS—MAX6066, V_{OUT} = 2.500V

(V_{IN} = +5V, I_{OUT} = 0, T_A = T_{MIN} to T_{MAX}, unless otherwise noted. Typical values are at T_A = +25°C.) (Note 1)

PARAMETER	SYMBOL	CONDITIONS		MIN	TYP	MAX	UNITS
Output Voltage	V _{OUT}	T _A = +25°C	MAX6066A (0.2%)	2.495	2.500	2.505	V
			MAX6066B (0.4%)	2.490	2.500	2.510	
Output Voltage Temperature Coefficient (Note 2)	TCV _{OUT}	MAX6066A		6	20	ppm/°C	
		MAX6066B		6	30		
Line Regulation	ΔV _{OUT} / ΔV _{IN}	(V _{OUT} + 0.2V) ≤ V _{IN} ≤ 12.6V		60	300	μV/V	
Load Regulation	ΔV _{OUT} / ΔI _{OUT}	Sourcing: 0 ≤ I _{OUT} ≤ 5mA		0.5	0.9	mV/mA	
		Sinking: -2mA ≤ I _{OUT} ≤ 0		1.6	5		
Dropout Voltage (Note 4)	V _{IN} - V _{OUT}	I _{OUT} = 1mA		50	200	mV	
OUT Short-Circuit Current	I _{SC}	Short to GND		25	mA		
		Short to IN		25			
Long-Term Stability	ΔV _{OUT} / time	1000hr at +25°C		62		ppm/ 1000hr	
Output Voltage Hysteresis (Note 3)	ΔV _{OUT} / cycle			130		ppm	
DYNAMIC CHARACTERISTICS							
Noise Voltage	e _{OUT}	f = 0.1Hz to 10Hz		27		μVp-p	
		f = 10Hz to 10kHz		30		μVRMS	
Ripple Rejection	ΔV _{OUT} / ΔV _{IN}	V _{IN} = 5V ±100mV, f = 120Hz		86		dB	
Turn-On Settling Time	t _R	To V _{OUT} = 0.1% of final value, C _{OUT} = 50pF		115		μs	
INPUT CHARACTERISTICS							
Supply Voltage Range	V _{IN}	Guaranteed by line-regulation test		V _{OUT} + 0.2	12.6	V	
Quiescent Supply Current	I _{IN}			90	125	μA	
Change in Supply Current	I _{IN} /V _{IN}	(V _{OUT} + 0.2V) ≤ V _{IN} ≤ 12.6V		3.3	8.0	μA/V	

Precision, Micropower, Low-Dropout, High-Output-Current, SOT23 Voltage References

ELECTRICAL CHARACTERISTICS—MAX6063, V_{OUT} = 3.0V

(V_{IN} = +5V, I_{OUT} = 0, T_A = T_{MIN} to T_{MAX}, unless otherwise noted. Typical values are at T_A = +25°C.) (Note 1)

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS
Output Voltage	V _{OUT}	T _A = +25°C	MAX6063A (0.2%)	2.994	3.000	3.006
			MAX6063B (0.4%)	2.988	3.000	3.012
Output Voltage Temperature Coefficient (Note 2)	TCV _{OUT}	MAX6063A		6	20	ppm/°C
		MAX6063B		6	30	
Line Regulation	ΔV _{OUT} / ΔV _{IN}	(V _{OUT} + 0.2V) ≤ V _{IN} ≤ 12.6V		90	400	μV/V
Load Regulation	ΔV _{OUT} / ΔI _{OUT}	Sourcing: 0 ≤ I _{OUT} ≤ 5mA		0.5	0.9	mV/mA
		Sinking: -2mA ≤ I _{OUT} ≤ 0		2.0	6.0	
Dropout Voltage (Note 4)	V _{IN} - V _{OUT}	I _{OUT} = 1mA		50	200	mV
OUT Short-Circuit Current	I _{SC}	Short to GND		25		mA
		Short to IN		25		
Long-Term Stability	ΔV _{OUT} / time	1000hr at +25°C		62		ppm/ 1000hr
Output Voltage Hysteresis (Note 3)	ΔV _{OUT} / cycle			130		ppm
DYNAMIC CHARACTERISTICS						
Noise Voltage	e _{OUT}	f = 0.1Hz to 10Hz		35		μVp-p
		f = 10Hz to 10kHz		40		μVRMS
Ripple Rejection	ΔV _{OUT} / ΔV _{IN}	V _{IN} = 5V ± 100mV, f = 120Hz		76		dB
Turn-On Settling Time	t _R	To V _{OUT} = 0.1% of final value, C _{OUT} = 50pF		115		μs
INPUT CHARACTERISTICS						
Supply Voltage Range	V _{IN}	Guaranteed by line-regulation test	V _{OUT} + 0.2	12.6		V
Quiescent Supply Current	I _{IN}			90	125	μA
Change in Supply Current	I _{IN} /V _{IN}	(V _{OUT} + 0.2V) ≤ V _{IN} ≤ 12.6V		3.4	8.0	μA/V

Precision, Micropower, Low-Dropout, High-Output-Current, SOT23 Voltage References

ELECTRICAL CHARACTERISTICS—MAX6064, V_{OUT} = 4.096V

(V_{IN} = +5V, I_{OUT} = 0, T_A = T_{MIN} to T_{MAX}, unless otherwise noted. Typical values are at T_A = +25°C.) (Note 1)

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS
Output Voltage	V _{OUT}	T _A = +25°C	MAX6064A (0.2%)	4.088	4.096	4.104
			MAX6064B (0.4%)	4.080	4.096	4.112
Output Voltage Temperature Coefficient (Note 2)	TCV _{OUT}	MAX6064A			6	20
		MAX6064B			6	30
Line Regulation	ΔV _{OUT} / ΔV _{IN}	(V _{OUT} + 0.2V) ≤ V _{IN} ≤ 12.6V			130	430
Load Regulation	ΔV _{OUT} / ΔI _{OUT}	Sourcing: 0 ≤ I _{OUT} ≤ 5mA			0.5	0.9
		Sinking: -2mA ≤ I _{OUT} ≤ 0			2.2	8
Dropout Voltage (Note 4)	V _{IN} - V _{OUT}	I _{OUT} = 1mA			50	200
OUT Short-Circuit Current	I _{SC}	Short to GND			25	mA
		Short to IN			25	
Long-Term Stability	ΔV _{OUT} / time	1000hr at +25°C			62	ppm/ 1000hr
Output Voltage Hysteresis (Note 3)	ΔV _{OUT} / cycle					ppm
DYNAMIC CHARACTERISTICS						
Noise Voltage	e _{OUT}	f = 0.1Hz to 10Hz			50	μVp-p
		f = 10Hz to 10kHz			50	μVRMS
Ripple Rejection	ΔV _{OUT} / ΔV _{IN}	V _{IN} = 5V ± 100mV, f = 120Hz			72	dB
Turn-On Settling Time	t _R	To V _{OUT} = 0.1% of final value, C _{OUT} = 50pF			190	μs
INPUT CHARACTERISTICS						
Supply Voltage Range	V _{IN}	Guaranteed by line-regulation test	V _{OUT} + 0.2	12.6		
Quiescent Supply Current	I _{IN}			90	125	μA
Change in Supply Current	I _{IN} /V _{IN}	(V _{OUT} + 0.2V) ≤ V _{IN} ≤ 12.6V	3.2	8.0		

Precision, Micropower, Low-Dropout, High-Output-Current, SOT23 Voltage References

ELECTRICAL CHARACTERISTICS—MAX6067, V_{OUT} = 4.500V

(V_{IN} = +5V, I_{OUT} = 0, T_A = T_{MIN} to T_{MAX}, unless otherwise noted. Typical values are at T_A = +25°C.) (Note 1)

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS
Output Voltage	V _{OUT}	T _A = +25°C	MAX6067A (0.2%)	4.491	4.500	4.509
			MAX6067B (0.4%)	4.482	4.500	4.518
Output Voltage Temperature Coefficient (Note 2)	TCV _{OUT}	MAX6067A		6	20	ppm/°C
		MAX6067B		6	30	
Line Regulation	ΔV _{OUT} / ΔV _{IN}	(V _{OUT} + 0.2V) ≤ V _{IN} ≤ 12.6V		170	550	µV/V
Load Regulation	ΔV _{OUT} / ΔI _{OUT}	Sourcing: 0 ≤ I _{OUT} ≤ 5mA		0.5	0.9	mV/mA
		Sinking: -2mA ≤ I _{OUT} ≤ 0		2.4	8	
Dropout Voltage (Note 4)	V _{IN} - V _{OUT}	I _{OUT} = 1mA		50	200	mV
OUT Short-Circuit Current	I _{SC}	Short to GND	25			mA
		Short to IN	25			
Long-Term Stability	ΔV _{OUT} / time	1000hr at +25°C		62		ppm/ 1000hr
Output Voltage Hysteresis (Note 3)	ΔV _{OUT} / cycle			130		ppm
DYNAMIC CHARACTERISTICS						
Noise Voltage	e _{OUT}	f = 0.1Hz to 10Hz	55			µVp-p
		f = 10Hz to 10kHz	55			µVRMS
Ripple Rejection	ΔV _{OUT} / ΔV _{IN}	V _{IN} = 5V ±100mV, f = 120Hz	70			dB
Turn-On Settling Time	t _R	To V _{OUT} = 0.1% of final value, C _{OUT} = 50pF	230			µs
INPUT CHARACTERISTICS						
Supply Voltage Range	V _{IN}	Guaranteed by line-regulation test	V _{OUT} + 0.2	12.6		V
Quiescent Supply Current	I _{IN}		90	125		µA
Change in Supply Current	I _{IN} /V _{IN}	(V _{OUT} + 0.2V) ≤ V _{IN} ≤ 12.6V	3.2	8.0		µA/V

Precision, Micropower, Low-Dropout, High-Output-Current, SOT23 Voltage References

ELECTRICAL CHARACTERISTICS—MAX6065, V_{OUT} = 5.000V

(V_{IN} = +5.2V, I_{OUT} = 0, T_A = T_{MIN} to T_{MAX}, unless otherwise noted. Typical values are at T_A = +25°C.) (Note 1)

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS
Output Voltage	V _{OUT}	T _A = +25°C	MAX6065A (0.2%)	4.990	5.000	5.010
			MAX6065B (0.4%)	4.980	5.000	5.020
Output Voltage Temperature Coefficient (Note 2)	TCV _{OUT}	MAX6065A		6	20	ppm/°C
		MAX6065B		6	30	
Line Regulation	ΔV _{OUT} / ΔV _{IN}	(V _{OUT} + 0.2V) ≤ V _{IN} ≤ 12.6V		180	550	μV/V
Load Regulation	ΔV _{OUT} / ΔI _{OUT}	Sourcing: 0 ≤ I _{OUT} ≤ 5mA		0.5	0.9	mV/mA
		Sinking: -2mA ≤ I _{OUT} ≤ 0		2.4	8.0	
Dropout Voltage (Note 4)	V _{IN} - V _{OUT}	I _{OUT} = 1mA		50	200	mV
OUT Short-Circuit Current	I _{SC}	Short to GND		25		mA
		Short to IN		25		
Long-Term Stability	ΔV _{OUT} / time	1000hr at +25°C		62		ppm/ 1000hr
Output Voltage Hysteresis (Note 3)	ΔV _{OUT} / cycle			130		ppm
DYNAMIC CHARACTERISTICS						
Noise Voltage	e _{OUT}	f = 0.1Hz to 10Hz		60		μVp-p
		f = 10Hz to 10kHz		60		μVRMS
Ripple Rejection	ΔV _{OUT} / ΔV _{IN}	V _{IN} = 5V ± 100mV, f = 120Hz		65		dB
Turn-On Settling Time	t _R	To V _{OUT} = 0.1% of final value, C _{OUT} = 50pF		300		μs
INPUT CHARACTERISTICS						
Supply Voltage Range	V _{IN}	Guaranteed by line-regulation test	V _{OUT} + 0.2	12.6		V
Quiescent Supply Current	I _{IN}			90	125	μA
Change in Supply Current	I _{IN} /V _{IN}	(V _{OUT} + 0.2V) ≤ V _{IN} ≤ 12.6V		3.2	8.0	μA/V

Note 1: All devices are 100% production tested at T_A = +25°C and are guaranteed by design for T_A = T_{MIN} to T_{MAX}, as specified.

Note 2: Temperature Coefficient is measured by the "box" method, i.e., the maximum ΔV_{OUT} is divided by the maximum ΔT.










Note 3: Temperature Hysteresis is defined as the change in +25°C output voltage before and after cycling the device from T_{MIN} to T_{MAX}.

Note 4: Dropout voltage is the minimum input voltage at which V_{OUT} changes ≤ 0.2% from V_{OUT} at V_{IN} = 5.0V (V_{IN} = 5.5V for MAX6065).

Precision, Micropower, Low-Dropout, High-Output-Current, SOT23 Voltage References

Typical Operating Characteristics










($V_{IN} = +5V$ for MAX6061–MAX6068, $V_{IN} = +5.5V$ for MAX6065, $I_{OUT} = 0$, $T_A = +25^\circ C$, unless otherwise noted.) (Note 5)



Precision, Micropower, Low-Dropout, High-Output-Current, SOT23 Voltage References

Typical Operating Characteristics (continued)

($V_{IN} = +5V$ for MAX6061–MAX6068, $V_{IN} = +5.5V$ for MAX6065, $I_{OUT} = 0$, $T_A = +25^\circ C$, unless otherwise noted.) (Note 5)









MAX6061–MAX6068

Precision, Micropower, Low-Dropout, High-Output-Current, SOT23 Voltage References

Typical Operating Characteristics (continued)







($V_{IN} = +5V$ for MAX6061–MAX6068, $V_{IN} = +5.5V$ for MAX6065, $I_{OUT} = 0$, $T_A = +25^\circ C$, unless otherwise noted.) (Note 5)



Precision, Micropower, Low-Dropout, High-Output-Current, SOT23 Voltage References

Typical Operating Characteristics (continued)


($V_{IN} = +5V$ for MAX6061–MAX6068, $V_{IN} = +5.5V$ for MAX6065, $I_{OUT} = 0$, $T_A = +25^\circ C$, unless otherwise noted.) (Note 5)



Precision, Micropower, Low-Dropout, High-Output-Current, SOT23 Voltage References

Typical Operating Characteristics (continued)

($V_{IN} = +5V$ for MAX6061–MAX6068, $V_{IN} = +5.5V$ for MAX6065, $I_{OUT} = 0$, $T_A = +25^\circ C$, unless otherwise noted.) (Note 5)



Note 5: Many of the MAX6061 family *Typical Operating Characteristics* are extremely similar. The extremes of these characteristics are found in the MAX6061 (1.25V output) and the MAX6065 (5.0V output). The *Typical Operating Characteristics* of the remainder of the MAX6061 family, typically lie between these two extremes and can be estimated based on their output voltages.

Precision, Micropower, Low-Dropout, High-Output-Current, SOT23 Voltage References

Pin Description

PIN	NAME	FUNCTION
1	IN	Input Voltage
2	OUT	Reference Output
3	GND	Ground

Applications Information

Input Bypassing

For the best line-transient performance, decouple the input with a $0.1\mu\text{F}$ ceramic capacitor as shown in the *Typical Operating Circuit*. Locate the capacitor as close to IN as possible. Where transient performance is less important, no capacitor is necessary.


Output/Load Capacitance

Devices in the MAX6061 family do not require an output capacitance for frequency stability. In applications where the load or the supply can experience step changes, an output capacitor of at least $0.1\mu\text{F}$ will reduce the amount of overshoot (undershoot) and improve the circuit's transient response. Many applications do not require an external capacitor, and the MAX6061 family can offer a significant advantage in these applications when board space is critical.

Supply Current

The quiescent supply current of the series-mode MAX6061 family is typically $90\mu\text{A}$ and is virtually independent of the supply voltage, with only an $8\mu\text{A}/\text{V}$ (max) variation with supply voltage. Unlike series references, shunt-mode references operate with a series resistor connected to the power supply. The quiescent current of a shunt-mode reference is thus a function of the input voltage. Additionally, shunt-mode references have to be biased at the maximum expected load current, even if the load current is not present at the time. In the MAX6061 family, the load current is drawn from the input voltage only when required, so supply current is not wasted and efficiency is maximized at all input voltages. This improved efficiency reduces power dissipation and extends battery life. When the supply voltage is below the minimum specified input voltage (as during turn-on), the devices can draw up to $400\mu\text{A}$ beyond the nominal supply current. The input voltage source must be capable of providing this current to ensure reliable turn-on.

Typical Operating Circuit



Ordering Information (continued)

PART	TEMP. RANGE	PIN-PACKAGE	TOP MARK
MAX6067AEUR-T	-40°C to +85°C	3 SOT23-3	FZFS
MAX6067BEUR-T	-40°C to +85°C	3 SOT23-3	FZFT
MAX6068AEUR-T	-40°C to +85°C	3 SOT23-3	FZIB
MAX6068BEUR-T	-40°C to +85°C	3 SOT23-3	FZIC

Output Voltage Hysteresis

Output voltage hysteresis is the change of output voltage at $T_A = +25^\circ\text{C}$ before and after the device is cycled over its entire operating temperature range. Hysteresis is caused by differential package stress appearing across the bandgap core transistors. The typical temperature hysteresis value is 130ppm.

Turn-On Time

These devices typically turn on and settle to within 0.1% of their final value in $50\mu\text{s}$ to $300\mu\text{s}$, depending on the device. The turn-on time can increase up to 1.5ms with the device operating at the minimum dropout voltage and the maximum load.

Chip Information

TRANSISTOR COUNT: 117

PROCESS: BiCMOS


Precision, Micropower, Low-Dropout, High-Output-Current, SOT23 Voltage References

Package Information


SOT23-3LFS

NOTES:

1. D&E DO NOT INCLUDE MOLD FLASH.
2. MOLD FLASH OR PROTRUSIONS NOT TO EXCEED .15mm (.006")
3. CONTROLLING DIMENSION: MILLIMETER



DIM	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	0.031	0.047	0.787	1.194
A1	0.001	0.005	0.025	0.127
B	0.014	0.022	0.356	0.559
C	0.0034	0.006	0.086	0.152
D	0.105	0.120	2.667	3.048
E	0.047	0.055	1.194	1.397
e	0.070	0.080	1.778	2.032
H	0.082	0.098	2.083	2.489
L	0.004	0.012	0.102	0.305
S	0.017	0.022	0.432	0.559
α	0°	8°	0°	8°



Maxim cannot assume responsibility for use of any circuitry other than circuitry entirely embodied in a Maxim product. No circuit patent licenses are implied. Maxim reserves the right to change the circuitry and specifications without notice at any time.

16 **Maxim Integrated Products, 120 San Gabriel Drive, Sunnyvale, CA 94086 408-737-7600**

© 2001 Maxim Integrated Products

Printed USA

MAXIM is a registered trademark of Maxim Integrated Products.