



NOTE: (1) per dimensioni fori e cave vedere foglio 10-019E / (2) le frecce ► indicano entrata e uscita del moto

ROTOFLUID GRANDEZZA	NY-FB														NY-SCF FB		NY-DCF FB		
	Dimensioni in mm														kg*	mm	kg*	mm	kg*
	D ⁶⁷	A	B	B1	C	G ^{h7}	N	M	R	S	T	T2	X1	Y	Peso	C1	Peso	C2	Peso
30	28 38 42-48-55	290	150	51	261	38	116	80	10	41	45	60	69	55	19	316	21,5	356	22,1
30P	28 38 42-48-55	327											64						
40P	38 42-48-55	338	183	61	324	48	145	91	14	51,5	55	80	104	72	31	382	35	454	37
50	42-48-55 60-65-75	430	154	71	325	55	165	110	16	59	65	100	106	91	44	405	50	480	52
55	42-48-55 60-65-75		196		367									77					
60	48-55 60-65-75 80	520	172	86	368	60	185	135	18	64	80	110	116	106	71	458	79	538	83
65	55 60-65-75 80		220		416						92			91					
70P	65-75 80-90 100	640	190	96	426	70	225	160	20	74,5	90	140	140	111	129	536	142	651	149
•75P	65-75 80-90 100		245		481					96				170					
80P	60-65-75 80-90 100-110	810	226	116	482	80	270	170	22	85	110	170	170	131	238	600	254	700	266
•85P	60-65-75 80-90 100-110		300		556									116					
90P	80-90-95 100-110 120-140	1000	344	186	700	110	345	250	28	116	180	170	170	240	470	760	510	840	530

* Peso con olio

DIMENSIONI NON IMPEGNATIVE

● Forniti con CAMERA MAGGIORATA SCFM o DCFM

Esempi di ordinazione: ALFA 55 NY-FB D=65
ALFA 55 NY-SCF FB D=65
ALFA 55 NY-DCF FB D=65