
GG44M Female thread coupling

Female BSPP thread (ISO 1179-1)



	Thread BSPP T4	C mm	L mm	Weight (steel) g/1 piece	Adapter Steel	Adapter Stainless Steel	PN (bar)
ľ	1/8	14	19	16	1/8GG44MS	1/8GG44MSS	420
	1/4	17	28	30	1/4GG44MS	1/4GG44MSS	420
	3/8	22	28	47	3/8GG44MS	3/8GG44MSS	420
	1/2	27	33	78	1/2GG44MS	1/2GG44MSS	350
	3/4	32	37	105	3/4GG44MS	3/4GG44MSS	280
	1	43	42	341	1GG44MS	1GG44MSS	210

Order codes shown are part of our current manufacturing programme. Imperial and metric parts may vary in hexagon dimensions.


$$\frac{PN \text{ (bar)}}{10} = PN \text{ (MPa)}$$

Pressure ratings – PN shown, apply to Steel and Stainless Steel versions of the product.



MMO444M Female thread tee

Female BSPP threads (ISO 1179-1)



Thread BSPP T4	A mm	Y mm	Weight (steel) g/1 piece	Adapter Steel	PN (bar)
1/4	22	19	74	1/4MMO444MS	350
3/8	26	22	111	3/8MMO444MS	315
1/2	31	27	177	1/2MMO444MS	210
3/4	40	33	294	3/4MMO444MS	210
1	46	41	567	1MMO444MS	120

Order codes shown are part of our current manufacturing programme. Imperial and metric parts may vary in hexagon dimensions.

$$\frac{PN (bar)}{10} = PN (MPa)$$

Pressure ratings – PN shown, apply to the Steel version of the product.

