

# CS1774



- 4-Port USB 2.0 KVME™ Switch
- CS1774 is a multi-computer KVM Switch with built-in 3-in-1 (KVM Switch, USB 2.0 and Ethernet) function. It can simultaneously control 4 servers via a set of USB keyboard, mouse, and monitor. Moreover, the built-in USB and Ethernet Switch ports can rapidly access USB peripheral devices and share Internet resources at ease.




## Features

- USB 2.0 KVME™ Switch with Ethernet Hub/USB Hub
- Five auto-sensing dual speed ports (Ethernet/Fast Ethernet) plug-and-play enabled; hub complies with IEEE802.3/IEEE802.3u Standard
- 2 port USB 2.0 Hub built in
- Multiplatform support: compatible with all operation platforms PC(Windows,Linux and most others), Mac and Sun
- With speaker and microphone support
- [Bi-directional switching and flexible interoperability;switch permits independent PC, independent peripheral, and independent audio function, regardless of KVM switch focus](#)
- Buzzer On/Off via hotkey
- Keyboard and mouse emulation for error free booting
- Computer selection via front panel pushbuttons and hotkeys
- superior video quality - up to 2048 x 1536; DDC2B
- OS Compatibility:Windows 98, Windows ME, Windows 2000, Windows 2003, Windows XP, [Windows Vista](#), LINUX, Mac OS 8.6/9/10 and SUN Solaris 8/9.
- SUN/Mac keyboard support and emulation\*
  - \*1.PC keyboard combinations emulate SUN/Mac keyboards.
  - \*2.SUN/Mac keyboards only work with their own computers.

## Specification

Computer Connections		4	
Port Selection		Hotkeys, Pushbutton	
USB Port/ Audio Port Selection		Hotkey	
Connectors	Console Ports	Keyboard	1 x USB Type A Female (White)
		Video	1 x HDB-15 Female (Blue)
		Mouse	1 x USB Type A Female (White)
		Speaker	1 x Mini Stereo Jack Female (Green)
		Microphone	1 x Mini Stereo Jack Female (Pink)
	KVM Ports	Keyboard	4 x SPHD-15 Female (Green)
		Video	
		Mouse	
		Speaker	4 x Mini Stereo Jack Female (Green)
		Microphone	4 x Mini Stereo Jack Female (Pink)
	Ethernet Hub		5 x RJ-45 Female (Black)
	USB Hub		2 x USB Type A Female (White)
	F/W Upgrade		1 x RJ-11 Female (Black)
	Power		1 x DC Jack(Black)
Switches	Port	4 x Pushbutton	
LEDs	On Line / Selected	4 (Orange)	
	USB Link	4 (Green)	
	10/100 Mbps	5 (Green)	
	LINK(Ethernet)	5 (Green)	
Emulation	Keyboard/Mouse	USB	
Video		2048 x 1536; DDC2B	
Scan Interval		1~99 seconds	
Power Consumption		DC 5.3V, 5W	
Environment	Operating Temp.	0°~50°C	
	Storage Temp.	-20°~60°C	
	Humidity	0~80% RH, Non-condensing	
Physical Properties	Housing	Metal	
	Weight	0.92 kg	
	Dimensions ( L x W x H )	27.00 x 8.70 x 5.50 cm	

# Diagram



**ATEN International Co., Ltd.**

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan  
 Phone: 886-2-8692-6789 Fax: 886-2-8692-6767  
 www.aten.com E-mail: marketing@aten.com

© Copyright 2012 ATEN® International Co., Ltd.  
 ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.  
 All rights reserved. All other trademarks are the property of their respective owners.