

2-channel soldering/desoldering station, integrated pump, MFR-H5-DS + MFR-H1-SC2

Description

- integrated pump with 0.7 bar vacuum force
- smartheat technology
- simple desoldering of push-through components and damage to printed circuit boards are reliably avoided
- large pilot collecting chamber
- Quick-change device for exchanging the solder collecting chamber

Product details

item number	WL27221
manufacturer	OKI
manufacturer item number	MFR-1351
model	MFR-1351
dimensions (LxWxH)	200 mm x 170 mm x 152.5 mm
scope of supply	MFR-PS1300: Dual Output Power Supply with Internal Pump MFR-H5-DS: desoldering handpiece, with selectable handle MFR-H1-SC2: New Style solder cartridge handpiece, with cable MFR-WSDSU: Universal storage stand for desoldering handpiece WS1: Universal stand for soldering handpiece
order unit	piece
product series	MFR series
frequency	450 KHz
voltage	100–240 V
vacuum	0,7 bar
suitable tips	SxP soldering tips, RxP rework cartridges, DxP desoldering tips
output power supply unit	60 Watt

station type	desoldering station, soldering station
included handpiece	MFR-H5-DS, MFR-H1-SC2
Tip to ground resistance	< 2 Ohm
temperature stability °C	+/- 1,1 °C
ambient operating temperature	10–40 °C
length cable	1.22 m
power consumption	110 W